

According to Regulation (EC) No. 1907/2006 (REACH)

XO1236D Diesel Anti Wax

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1	.1	Product id	lentifier

Product name: XO1236D Diesel Anti Wax

Trade name(s): Tincknell Diesel Anti Wax (XO1236D)

Product description: Liquid fuel additive

CAS No.:

EC No.:

Index No.:

Not applicable.

Not applicable.

Not applicable.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified use(s): Liquid fuel additive.

Uses advised against: Follow supplier's recommendations on correct use of the

product.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Fuel Additive Science Technologies Limited

Unit 29, Atcham Business Park, Upton Magna, Shrewsbury, Shropshire, SY4 4UG

Telephone: +44 1743 761415

E-mail: info@fastexocet.co.uk

1.4 Emergency telephone number

In case of emergency, call: 0844 560 5135 (24 hours, 7 days)



According to Regulation (EC) No. 1907/2006 (REACH)

SECTION 2: Hazard Identification

2.1 Classification of the substance or mixture

2.1.1. Classification according to Regulation (EC) No. 1272/2008 (CLP)

Asp Tox 1 H304 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Carc. 2; H351

Aquatic Chronic 2; H411

EUH066

2.1.2. Classification according to Directive 67/548/EEC & Directive 1999/45/EC

Irritant; Xi; R36/38 Carc. Cat. 3; Xn; R40 Harmful; Xn; R65

R66

Dangerous for the environment; N; R51/53

2.2 Label elements

2.2.1. Label according to Regulation (EC) No. 1272/2008 (CLP)

Hazard pictogram(s):



Signal Word: Danger.

Hazard Statement(s): H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H319: Causes serious eye irritation. H351: Suspected of causing cancer.

H411: Toxic to aquatic life with long lasting effects.

Precautionary Statement(s): P201: Obtain special instructions before use.

P281: Use personal protective equipment as required.





P301 + P310: IF SWALLOWED: Immediately call a

POISON CENTER or doctor/physician.

P331: Do NOT induce vomiting.

P405: Store locked up.

P501: Dispose of contents/container to hazardous waste collection point for disposal in accordance with local, regional, national or international regulations.

(EU):

Supplemental Hazard information EUH066: Repeated exposure may cause skin dryness or cracking.

2.2.2. Label according to Directive 67/548/EEC or Directive 1999/45/EC

Hazard symbol(s):





Indication(s) of danger: Harmful; Dangerous for the Environment.

Risk phrase(s): R36/38: Irritating to eyes and skin.

> R40: Limited evidence of a carcinogenic effect. R65: May cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or

cracking.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety Phrase(s): S1/2: Keep locked up and out of the reach of children.

S23: Do not breathe fumes/vapour.

S24/25: Avoid contact with skin and eyes.

S26: In case of contact with eyes, rinse immediately

with plenty of water and seek medical advice.

S29: Do not empty into drains.

S35: This material and its container must be disposed

of in a safe way.

S36: Wear suitable protective clothing.

S39: Wear eye/face protection.

S51: Use only in well-ventilated areas.



According to Regulation (EC) No. 1907/2006 (REACH)

S61: Avoid release to the environment. Refer to special

instructions/Safety Data Sheets.

S62: If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

2.3 Other hazards

None known.

SECTION 3: Composition

3.2 Mixtures

Classification according to Regulation (EC) No. 1272/2008 (CLP)

Chemical name	% w/w	CAS No.	EC No.	Index No.	Classification
Solvent naphtha (petroleum), heavy aromatic	30-50	64742-94-5	265-198-5	-	Asp. Tox. 1; H304 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Aquatic Chronic 2; H411
Fuels, diesel, No. 2	10-30	68476-34-6	270-676-1	-	Asp Tox 1; H304 Carc. 2; H351 Aquatic Chronic 2; H411 EUH066
Trimethylbenzene	10-15	25551-13-7	247-099-9	-	Flam. Liq. 3, H226 Acute Tox. 4; H302 Acute Tox 4; H312 Skin Irrit. 2; H315
Naphthalene	1-5	91-20-3	202-049-5	-	Carc. 2; H351 Acute Tox. 4; H302 Aquatic Acute 1; H400 Aquatic Chronic 1; H410

Classification according to Directive 67/548/EEC

Chemical name	% w/w	CAS No.	EC No.	Index No.	Classification
Solvent naphtha (petroleum), heavy aromatic	30-50	64742-94-5	265-198-5	-	Xi; R36/38 Xn; R65 N; R51/53
Fuels, diesel, No. 2	10-30	68476-34-6	270-676-1	-	Carc. Cat. 3; R40 Xn; R65 R66 N; R51/53



According to Regulation (EC) No. 1907/2006 (REACH)

Chemical name	% w/w	CAS No.	EC No.	Index No.	Classification
Trimethylbenzene	10-15	25551-13-7	247-099-9	-	Xn; R21/22 Xi; R38 R10
Naphthalene	1-5	91-20-3	202-049-5	-	Carc. Cat. 3; R40 Xn; R22 N; R50/53

See Section 16 for full description of R phrases and H statements.

SECTION 4: First Aid Measures

4.1 Description of first aid measures

INHALATION: Obtain immediate medical attention. Remove patient

from exposure, keep warm and at rest.

SKIN CONTACT: Remove contaminated clothing immediately. Rinse

affected area with copious amounts of water. Then wash area with soap and water for at least 15 minutes. If symptoms persist, obtain medical attention. Discard of or wash thoroughly contaminated clothing.

EYE CONTACT: Remove contact lenses if present and easy to do.

Wash eyes immediately with plenty of water for at least

15 minutes. Seek medical attention immediately.

INGESTION: Provided the patient is conscious wash mouth out with

water and provide patient with 200-300 ml of water to drink. Do not induce vomiting. Obtain medical attention

immediately.

4.2 Most important symptoms and effects, both acute and delayed:

Skin contact causes redness and pain. Repeated exposure may cause skin dryness or cracking. Eye contact causes watering, redness and pain. Inhalation of high concentrations of vapour may cause irritation to the respiratory tract. Ingestion may cause irritation to mouth, throat and digestive tract. If swallowed, aspiration into lungs may result in chemical pneumonia.

Suspected of causing cancer.





4.3 Indication of any immediate medical attention and special treatments needed:

In case of accident or if you feel unwell, seek medical advice immediately. If swallowed, patient should be monitored for signs of breathing difficulty as effects of aspiration may be delayed for up to 48 hours. If breathing is laboured, oxygen should be administered by qualified personnel.

SECTION 5: Fire-fighting Measures

5.1 Extinguishing Media

Suitable extinguishing media: Foam, CO2 or dry powder.

For large fires, use water.

Unsuitable extinguishing media: Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Combustible liquid and vapour. Vapour may form explosive mixture with air.

Combustion may liberate toxic fumes: Carbon monoxide, carbon dioxide, various hydrocarbons.

5.3 Advice for fire-fighters

A self-contained breathing apparatus and suitable protective clothing should be worn in fire conditions. Keep fire exposed containers cool by spraying with water. Do not allow to enter drains, sewers or watercourses.

Flash point: Approx. > 63 °C (closed cup).

SECTION 6: Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

Eliminate sources of ignition. Ensure adequate ventilation. Avoid contact with skin and eyes. Avoid breathing fumes/vapour. Wear suitable personal protective equipment. Wear appropriate respirator when ventilation is inadequate. (See section 8).

6.1.2 For emergency responders

Keep unnecessary personnel away. Wear suitable protective clothing (See Section 8). Contaminated clothing should be thoroughly cleaned.





6.2 Environmental precautions

Collect spillage. Do not allow to enter drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be alerted to the Environment Agency or other appropriate regulatory body.

6.3 Methods and materials for containment and clearing up

6.3.1 For containment

Stop the leak if it is safe to do so. Contain the spillage with sand, earth or any suitable adsorbent material.

6.3.2 For cleaning up

Use sand, earth or any suitable non-combustible adsorbent material to adsorb spillages. Using non-sparking tools transfer the contaminated absorbent material into a container for disposal. The containers used should be plastic-lined sealable drums. Containers should be sealed before being disposed of via an authorised waste disposal contractor.

6.3.3 Other advice

None.

6.4 Reference to other sections

See Section 8 for personal protective equipment. See Section 13 for waste disposal.

SECTION 7: Handling and Storage

7.1 Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Provide adequate ventilation, including local extraction to ensure occupational exposure limits are not exceeded. Avoid breathing fumes/vapour. Avoid contact with skin and eyes. Use intrinsically sound equipment. Wear suitable personal protective equipment (See Section 8).

Do not eat, drink or smoke in the vicinity of the product. Wash exposed skin after use. Contaminated clothing should be thoroughly cleaned or disposed of as hazardous waste.

7.2 Conditions for safe storage, including any incompatibilities

Keep away from heat and sources of ignition. Keep from direct sunlight. Store locked up. Store only in the original container. Store in a cool, well ventilated place. Maximum handling temperature: 50℃. Empty containers retain product residue and can be hazardous.

Keep away from oxidising agents.





7.3 Specific end uses(s)

Liquid fuel additive.

SECTION 8: Exposure Controls/Personal Protection

8.1 Control parameters

Workplace exposure limits

Source: EH40/2005.

Substance	CAS No.	LTEL (8 hr TWA)		STEL (15 min)		Commente
Substance		ppm	mg/m³	ppm	mg/m³	Comments
Trimethylbenzenes, all isomers or mixtures	25551-13-7	25	125	-	-	-

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Provide adequate ventilation, including local extraction to ensure occupational exposure limits are not exceeded.

8.2.2 Personal protection

Eye protection: Goggles giving complete protection to eyes. (EN 166)

Skin protection:

Hand protection: Chemical resistant gloves. (EN 374).

Other: Long sleeve protective clothing. Plastic apron. Rubber

boots.

Respiratory protection: In the case of insufficient ventilation, wear suitable

respiratory equipment. (BS EN 14387:2004+A1)

Thermal hazards: Wear suitable temperature resistant gloves and

protective clothing if the product is heated.

8.2.3 Environmental exposure controls

Inform environmental manager of all incidents involving this product.





SECTION 9: Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance: Colourless to yellowish liquid.

Odour: Aromatic.

Odour threshold: Not available.

pH: Not available.

Melting/freezing point:: Not available.

Initial boiling point and boiling range: 170 - 370 ℃

Flash point: > 63 °C (Closed cup)

Evaporation rate: Not available.

Flammability (solid; gas): Not applicable.

Upper/lower flammability or explosive limits: 0.5% - 6% (v/v)

Vapour pressure:Not available.Vapour density:Not available.

Relative density: $0.895 (15 ^{\circ}C) (Water = 1)$

Solubility(ies): Immiscible in water.

Miscible in aromatic solvents.

Partition coefficient: n-octanol/water:

Auto-ignition temperature:

Not available.

Not available.

Not available.

Viscosity:

Not available.

Explosive properties: Not explosive. Vapour may form explosive mixture with

air.

Oxidising properties: Not oxidising.

9.2 Other information

None.

SECTION 10: Stability and Reactivity

10.1 Reactivity Reacts with oxidising agents.

10.2 Chemical stability Stable under normal conditions.



According to Regulation (EC) No. 1907/2006 (REACH)

10.3 Possibility of hazardous reactions No hazardous reactions expected during normal use.

10.4 Conditions to avoid Keep away from sources of ignition, hot surfaces, direct

sunlight. Contact with incompatible materials.

10.5 Incompatible materials Oxidising agents.

10.6 Hazardous decomposition products Combustion may liberate toxic fumes: Carbon monoxide,

carbon dioxide, various hydrocarbons.

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity Ingestion may cause discomfort.

No data available on the mixture.

Skin corrosion/irritationCauses skin irritation.

Serious eye damage/irritation Causes serious eye irritation.

Skin sensitisationNo evidence of skin sensitisation.

Respiratory sensitisationNo evidence of respiratory sensitisation.

Germ cell mutagenicityNo evidence of mutagenicity.

Carcinogenicity Suspected of causing cancer.

Reproductive toxicityNo evidence of reproductive toxicity.

Specific Target Organ Toxicity - single

exposure

Inhalation of high concentrations of vapour may cause

irritation to the respiratory tract.

Specific Target Organ Toxicity –

repeated exposure

Based on the available data, the classification criteria

are not met.

Aspiration hazard May be fatal if swallowed and enters airways. Risk of

aspiration into lungs resulting in chemical pneumonia.

Information on likely routes of exposure

Inhalation Inhalation of high concentrations of vapour may cause

irritation to the respiratory tract.



According to Regulation (EC) No. 1907/2006 (REACH)

Skin contact Causes skin irritation. Repeated exposure may cause

skin dryness or cracking.

Eye contact Causes serious eye irritation.

Ingestion May be fatal if swallowed and enters airways. Risk of

aspiration into lungs resulting in chemical pneumonia.

Symptoms related to the physical, chemical

and toxicological characteristics

Skin contact causes redness and pain. Repeated exposure may cause skin dryness or cracking. Eye contact causes watering, redness and pain. Inhalation of high concentrations of vapour may cause irritation to the respiratory tract. Ingestion may cause irritation to mouth, throat and digestive tract. If swallowed, aspiration into

lungs may result in chemical pneumonia.

Mixture versus substance information No data available.

Other information None.

SECTION 12: Ecological Information

12.1 Toxicity Toxic to aquatic life with long lasting effects.

M factor: 1

12.2 Persistence and degradability No data available.

12.3 Bioaccumulative potential No data available.

12.4 Mobility in soil No data available.

12.5 Results of PBT and vPvB The product does not contain

assessment

The product does not contain substances assessed to

be PBT or vPvB.

12.6 Other adverse effects None known.

SECTION 13: Disposal Considerations

13.1 Waste treatment methods

To be disposed of as hazardous waste. Disposal should be in accordance with local, state or national legislation.

Contaminated adsorbent must be removed in sealed, plastic lined drums and disposed of via an authorised waste disposal contractor. Do not empty into drains; dispose of this material and its container in a safe way.



According to Regulation (EC) No. 1907/2006 (REACH)

SECTION 14: Transport Information

ADR					
14.1	UN Number	3082			
14.2	UN Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains naphthalene)			
14.3	Transport hazard class(es)	9			
14.4	Packing group	III			
14.5	Environmental hazards	Yes			
14.6	Special precautions for the user	Read SDS and supplier instructions on correct use of the product.			
ADN					
14.1	UN Number	3082			
14.2	UN Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains naphthalene)			
14.3	Transport hazard class(es)	9			
14.4	Packing group	III			
14.5	Environmental hazards	Yes			
14.6	Special precautions for the user	Read SDS and supplier instructions on correct use of the product.			
RID					
14.1	UN Number	3082			
14.2	UN Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains naphthalene)			
14.3	Transport hazard class(es)	9			
14.4	Packing group	III			
14.5	Environmental hazards	Yes			
14.6	Special precautions for the user	Read SDS and supplier instructions on correct use of the product.			
IATA/ICAO					
14.1	UN Number	3082			
14.2	UN Proper shipping name	Environmentally hazardous substance, liquid, n.o.s. (contains naphthalene)			
14.3	Transport hazard class(es)	9			

Version: 2.0 Date: 28/09/2012

14.4 Packing group

Ш



According to Regulation (EC) No. 1907/2006 (REACH)

14.5 Environmental hazards Yes

14.6 Special precautions for the user Read SDS and supplier instructions on correct use of

the product.

IMDG

14.1 UN Number 3082

14.2 UN Proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE,

LIQUID, N.O.S. (contains naphthalene)

14.3 Transport hazard class(es)

14.4 Packing group

14.5 Environmental hazards Marine pollutant.

14.6 Special precautions for the user Read SDS and supplier instructions on correct use of

the product.

14.7 Transport in bulk according to Annex II

of MARPOL 73/78 and the IBC code

The product is not intended to be transported in bulk.

SECTION 15: Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This Safety Data Sheet was prepared in accordance with EC Regulation (EC) No. 1907/2006 as amended. The product has been classified in accordance with Regulation (EC) No. 1272/2008 (CLP), Directive

67/548/EEC & Directive 1999/45/EC.

15.2 Chemical Safety Assessment

Not applicable.

SECTION 16: Other Information

Full text of relevant R-phrases and/or H-statements:

Hazard Statement(s): H226: Flammable liquid and vapour

H302: Harmful if swallowed

H304: May be fatal if swallowed and enters

Airways

H312: Harmful in contact with skin

H315: Causes skin irritation

H351: Suspected of causing cancer

H400: Very toxic to aquatic life

H410: Very toxic to aquatic life with long lasting effects

H411: Toxic to aquatic life with long lasting effects



According to Regulation (EC) No. 1907/2006 (REACH)

(EU):

Supplemental Hazard information EUH066: Repeated exposure may cause skin

dryness or cracking.

R10: Flammable. Risk phrase(s):

B21/22: Harmful in contact with skin and if swallowed.

R22: Harmful if swallowed. R38: Irritating to skin.

R40: Limited evidence of a carcinogenic effect. R50/53: Very toxic to aquatic organisms, may cause

long-term adverse effects in the aquatic

environment.

R51/53: Toxic to aquatic organisms, may cause

long-term adverse effects in the aquatic

environment.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin

dryness or cracking.

Abbreviations:

CAS: Chemical Abstracts Service:

EINECS: European Inventory of Existing Commercial Chemical Substances

PBT: Persistent, Bioaccumulative and Toxic. vPvB: Very Persistent and Very Bioaccumulative.

References:

Supplier's Safety Data Sheets for ingredients

Product formulation

Approved Classification and Labelling Guide (Sixth edition)

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 Regulation (EC) No. 1272/2008 of the European Parliament and of the council.

Disclaimer:

THE INFORMATION PRESENTED HEREIN IS BELIEVED TO BE ACCURATE. BUT IS NOT WARRANTED TO BE, WHETHER ORIGINATING WITH THE COMPANY OR NOT. RECIPIENTS ARE ADVISED TO CONFIRM. IN ADVANCE OF NEED. THAT THE INFORMATION IS CURRENT. APPLICABLE, AND SUITABLE TO THEIR CIRCUMSTANCES.

Version history:

Version: 2.0 XO1236D Diesel Anti Wax Page 15 of 15 Date: 28/09/2012



According to Regulation (EC) No. 1907/2006 (REACH)

Version: 2.0

Issue date: 28/09/2012

Previous Version: 1.0

Issue date of previous version: 08/11/2011

Sections changed from previous version: 1-16