According to Regulation (EC) No. 1907/2006 (REACH)

XO1535HO Premium Heating Oil Additive + Fragrance

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name: XO1535HO Premium Heating Oil Additive + Fragrance

(new formulation)

Trade name(s): Premium Heating Oil Additive + Fragrance (XO1535HO)

Product description: Liquid fuel additive

CAS No.:

EC No.:

Index No.:

Not applicable.

Not applicable.

Not applicable.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified use(s): Liquid fuel additive.

Uses advised against: Follow supplier's recommendations on correct use of the

product

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Fuel Additive Science Technologies Limited

Unit 29, Atcham Business Park, Upton Magna, Shrewsbury, Shropshire, SY4 4UG

Telephone: +44 1743 761415

E-mail: info@fastexocet.co.uk

1.4 Emergency telephone number

In case of emergency, call: 0844 560 5135 (24 hours, 7 days)





SECTION 2: Hazard Identification

2.1 Classification of the substance or mixture

2.1.1. Classification according to Regulation (EC) No. 1272/2008 (CLP)

Acute Tox 4; H302 Asp. Tox. 1; H304 Skin Irrit. 2; H315 Skin Sens. 1; H317 Eye Dam. 1; H318 Carc. 2; H351

Aquatic Chronic 2; H411

2.1.2. Classification according to Directive 67/548/EEC & Directive 1999/45/EC

Harmful; Xn; R22 Irritant; Xi; R38 Irritant; Xi; R41 Carc. Cat. 3; R40 Irritant; Xi; R43 Harmful; Xn; R65

Dangerous for the environment; N; R51/53

2.2 Label elements

2.2.1. Label according to Regulation (EC) No. 1272/2008 (CLP)

Hazard pictogram(s):



Signal Word: Danger.

Hazard Statement(s): H302: Harmful if swallowed.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage. H351: Suspected of causing cancer.

Version: 2.0 XO1535HO Premium Heating Oil Additive + Date: 10/10/2012 Fragrance



H411: Toxic to aquatic life with long lasting effects.

Precautionary Statement(s): P280: Wear protective gloves / protective clothing / eye

protection / face protection.

P301 + P310: IF SWALLOWED: Immediately call a

POISON CENTER or doctor/physician.

P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing. P310: Immediately call a POISON CENTER or

doctor/physician.

P331: Do NOT induce vomiting.

P405: Store locked up.

P501: Dispose of contents/container to: disposal should be in accordance with local, state or national legislation.

Supplemental Hazard information None. **(EU):**

2.2.2. Label according to Directive 67/548/EEC or Directive 1999/45/EC

Hazard symbol(s):





Indication(s) of danger: Harmful; Dangerous for the Environment.

Risk phrase(s): R22: Harmful if swallowed.

R38: Irritating to skin.

R41: Risk of serious damage to eyes.

R40: Limited evidence of a carcinogenic effect. R43: May cause sensitisation by skin contact. R65: May cause lung damage if swallowed.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety Phrase(s): S1/2: Keep locked up and out of the reach of children.

S13: Keep away from food, drink and animal feeding

Version: 2.0 Date: 10/10/2012



stuffs.

S23: Do not breathe fumes/vapour.

S24/25: Avoid contact with skin and eyes.

S26: In case of contact with eyes, rinse immediately

with plenty of water and seek medical advice.

S27: Take off immediately all contaminated clothing. S28: After contact with skin, wash immediately with

plenty of soap and water.

S29: Do not empty into drains.

S35: This material and its container must be disposed

of in a safe way.

S36: Wear suitable protective clothing.

S39: Wear eye/face protection.

S51: Use only in well-ventilated areas.

S61: Avoid release to the environment. Refer to special

instructions/Safety Data Sheets.

S62: If swallowed, do not induce vomiting: seek

medical advice immediately and show this container or

label.

2.3 Other hazards

None known.

SECTION 3: Composition

3.2 Mixtures

Version: 2.0

Date: 10/10/2012

Classification according to Regulation (EC) No. 1272/2008 (CLP)

Chemical name	% w/w	CAS No.	EC No.	Index No.	Classification
Solvent naphtha (petroleum), heavy arom. (f.p. > 60 °C)	20-40	64742-94-5	265-198-5	649-424-00-3	Asp. Tox. 1; H304 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Aquatic Chronic 2; H411
2,6-Di-tert-butylphenol	10-20	128-39-2	204-884-0	-	Eye Dam 1; H318 Aquatic Acute 1: H400 Aquatic Chronic 1; H410
Trimethylbenzene	10-20	25551-13-7	247-099-9	-	Flam Liq. 3; H226 Acute Tox 4; H302 Acute Tox 4; H312 Skin Irrit. 2; H315

XO1535HO Premium Heating Oil Additive + Fragrance



Chemical name	% w/w	CAS No.	EC No.	Index No.	Classification
Naphthalene	5-10	91-20-3	202-049-5	601-052-00-2	Acute Tox 4; H302 Carc 2; H351 Aquatic Acute 1: H400 Aquatic Chronic 1; H410
Solvent naphtha (petroleum), heavy arom. (f.p. < 60 °C)	1-5	64742-94-5	265-198-5	649-424-00-3	Flam. Liq. 3; H226 Asp. Tox. 1; H304 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Aquatic Chronic 2; H411
4-Hydroxy-3-methoxy- benzaldehyde	1-5	121-33-5	204-465-2	-	Skin Sens. 1; H317
Dicyclohexylamine	< 1	101-83-7	202-980-7	612-066-00-3	Acute Tox 3; H301 Acute Tox 3; H311 Skin Corr. 1B; H314 Aquatic Acute 1; H400
Pentyl salicylate	< 1	2050-08-0	218-080-2	-	Aquatic Chronic 2; H411
1,3,4,6,7,8-hexahydro- 4,6,6,7,8,8-hexa- methylindeno[5,6-c]- pyran	< 1	1222-05-5	214-946-9	-	Aquatic Acute 1; H400 Aquatic Chronic 1; H410
5-Heptyloxolan-2-one	< 1	104-67-6	203-225-4	-	Aquatic Chronic 2; H411
1,3,5-Trimethylbenzene	< 1	108-67-8	203-604-4	601-025-00-5	Flam. Liq. 3; H226 Eye Irrit. 2; H319 STOT SE 3; H335 Aquatic Chronic 2; H411
1,2,4-Trimethylbenzene	< 1	95-63-6	202-436-9	601-043-00-3	Flam. Liq. 3; H226 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Acute Tox. 4; H332 STOT SE 3; H335 Aquatic Chronic 2; H411

Classification according to Directive 67/548/EEC

Chemical name	% w/w	CAS No.	EC No.	Index No.	Classification
Solvent naphtha (petroleum), heavy arom. (f.p. > 60 ℃)	20-40	64742-94-5	265-198-5	649-424-00-3	Xi; R36/38 Xn; R65 N; R51/53
2,6-Di-tert-butylphenol	10-20	128-39-2	204-884-0	-	Xi; R41 N; R50/53
Trimethylbenzene	10-20	25551-13-7	247-099-9	-	R10 Xn; R21/22 Xi; R38



Chemical name	% w/w	CAS No.	EC No.	Index No.	Classification
Naphthalene	5-10	91-20-3	202-049-5	601-052-00-2	Xn; R22 Carc. Cat. 3; R40 N; R50/53
Solvent naphtha (petroleum), heavy arom. (f.p. < 60 ℃)	1-5	64742-94-5	265-198-5	649-424-00-3	Xi; R36/38 Xn; R65 N; R51/53
4-Hydroxy-3-methoxy- benzaldehyde	1-5	121-33-5	204-465-2	-	Xi; R43
Dicyclohexylamine	< 1	101-83-7	202-980-7	612-066-00-3	C; R34 T; R24/25 N; R50
Pentyl salicylate	< 1	2050-08-0	218-080-2	-	N; R51/53
1,3,4,6,7,8-hexahydro- 4,6,6,7,8,8-hexa- methylindeno[5,6-c]- pyran	< 1	1222-05-5	214-946-9	-	N; R50/53
5-Heptyloxolan-2-one	< 1	104-67-6	203-225-4	-	N; R51/53
1,3,5-Trimethylbenzene	< 1	108-67-8	203-604-4	601-025-00-5	C; R34 Xn; R22 N; R50/53
1,2,4-Trimethylbenzene	< 1	95-63-6	202-436-9	601-043-00-3	R10 Xn; R20 Xi; R36/37/38 N; R51/53

See Section 16 for full description of R phrases and H statements.

SECTION 4: First Aid Measures

4.1 Description of first aid measures

INHALATION: Remove patient form exposure, keep warm and at rest.

If symptoms persist, obtain medical attention.

SKIN CONTACT: Remove contaminated clothing immediately. Rinse

affected area with copious amounts of water. Then wash area with soap and water for at least 30 minutes. If symptoms persist, obtain medical attention. Discard of or wash thoroughly contaminated clothing.

EYE CONTACT: Obtain immediate medical attention. Remove contact

lenses if present and easy to do. Wash eyes

Version: 2.0 Date: 10/10/2012



immediately with plenty of water for at least 30 minutes.

INGESTION: Obtain immediate medical attention. Provided the

patient is conscious wash mouth out with water and provide patient with 200-300 ml of water to drink. Do

not induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed:

Skin contact causes redness and pain. Skin contact may cause rash. Eye contact causes burns, watering, redness and pain. Inhalation of high concentrations of vapour may cause irritation to the respiratory tract. Ingestion may cause irritation to mouth, throat and digestive tract. If swallowed, aspiration into lungs may result in chemical pneumonia.

Suspected of causing cancer.

4.3 Indication of any immediate medical attention and special treatments needed:

In case of accident or if you feel unwell, seek medical advice immediately. If in contact with eyes, wash eyes immediately and seek immediate medical attention. If swallowed, patient should be monitored for signs of breathing difficulty as effects of aspiration may be delayed for up to 48 hours. If breathing is laboured, oxygen should be administered by gualified personnel.

SECTION 5: Fire-fighting Measures

5.1 Extinguishing Media

Suitable extinguishing media: Foam, CO2 or dry powder.

For large fires, use water.

Unsuitable extinguishing media: Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Combustible liquid and vapour. Vapour may form explosive mixture with air.

Combustion may liberate toxic fumes: Carbon monoxide, carbon dioxide, various hydrocarbons.

5.3 Advice for fire-fighters

A self-contained breathing apparatus and suitable protective clothing should be worn in fire conditions. Keep fire exposed containers cool by spraying with water. Do not allow to enter drains, sewers or watercourses.

Flash point: > 61 °C (closed cup).



SECTION 6: Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

Eliminate sources of ignition. Ensure adequate ventilation. Avoid contact with skin and eyes. Avoid inhalation of fumes/vapours. Wear suitable personal protective equipment. Wear appropriate respirator when ventilation is inadequate. (See section 8).

6.1.2 For emergency responders

Keep unnecessary personnel away. Wear suitable protective clothing (See Section 8). Contaminated clothing should be thoroughly cleaned.

6.2 Environmental precautions

Collect spillage. Do not allow to enter drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be alerted to the Environment Agency or other appropriate regulatory body.

6.3 Methods and materials for containment and clearing up

6.3.1 For containment

Stop the leak if it is safe to do so. Contain the spillage with sand, earth or any suitable adsorbent material.

6.3.2 For cleaning up

Use sand, earth or any suitable non-combustible adsorbent material to adsorb spillages. Using non-sparking tools transfer the contaminated absorbent material into a container for disposal. The containers used should be plastic-lined sealable drums. Containers should be sealed before being disposed of via an authorised waste disposal contractor.

6.3.3 Other advice

None.

6.4 Reference to other sections

See Section 8 for personal protective equipment. See Section 13 for waste disposal.

SECTION 7: Handling and Storage

7.1 Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Provide adequate ventilation, including local extraction to ensure the occupational

Version: 2.0 XO1535HO Premium Heating Oil Additive + Date: 10/10/2012 Fragrance



exposure limit is not exceeded. Avoid inhalation of fumes/vapours. Avoid contact with skin and eyes. Wear suitable personal protective equipment (See Section 8).

Do not eat, drink or smoke when using this product. Wash exposed skin after use. Contaminated work clothing should not be allowed out of the workplace. Contaminated clothing should be thoroughly cleaned or disposed of as hazardous waste.

7.2 Conditions for safe storage, including any incompatibilities

Keep away from heat and sources of ignition. Keep from direct sunlight. Store locked up. Store only in the original container. Store in a cool, well ventilated place. Maximum handling temperature: 50 ℃. Empty containers retain product residue and can be hazardous.

Keep away from oxidising agents.

7.3 Specific end uses(s)

Liquid fuel additive.

SECTION 8: Exposure Controls/Personal Protection

8.1 Control parameters

Workplace exposure limits

Source: EH40/2005, 2nd Ed., 2011.

Substance	CACNA	LTEL (8 hr TWA)		STEL (15 min)		
Substance	CAS No.	ppm	mg/m³	ppm	mg/m³	Comments
Trimethylbenzenes, all isomers or mixtures	25551-13-7	25	125	-	-	-

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction.

8.2.2 Personal protection

Eye protection: Goggles giving complete protection to eyes. (EN 166)

Skin protection:

Hand protection: Chemical resistant gloves. (EN 374).

Other: Long sleeve protective clothing. Plastic apron. Rubber

Version: 2.0 XO1535HO Premium Heating Oil Additive + Date: 10/10/2012 Fragrance

According to Regulation (EC) No. 1907/2006 (REACH)

boots.

Respiratory protection: In the case of insufficient ventilation, wear suitable

respiratory equipment. (BS EN 14387:2004+A1)

Thermal hazards: Wear suitable temperature resistant gloves and

protective clothing if the product is heated.

8.2.3 Environmental exposure controls

Inform environmental manager of all incidents involving this product.

SECTION 9: Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance: Brown liquid.

Odour: Hydrocarbon.

Odour threshold: Not available.

pH: Not available.

Melting/freezing point:: Not available.

Initial boiling point and boiling range: Not available.

Flash point: $> 61 \,^{\circ}\text{C}$ (Closed cup)

Evaporation rate:

Flammability (solid; gas):

Upper/lower flammability or explosive limits:

Vapour pressure:

Not available.

Not available.

Not available.

Not available.

Relative density: 0.89 - 1.04 (Water = 1) **Solubility(ies):** Immiscible in water.

Miscible in aromatic solvents.

Partition coefficient: n-octanol/water:

Auto-ignition temperature:

Not available.

Not available.

Not available.

Viscosity:

Not available.

Explosive properties: Not explosive. Vapour may form explosive mixture with

air

Oxidising properties: Not oxidising.



Tincknell Fuels Ltd

According to Regulation (EC) No. 1907/2006 (REACH)

9.2 Other information

None.

SECTION 10: Stability and Reactivity

10.1 Reactivity Reacts with oxidising agents.

10.2 Chemical stability Stable under normal conditions.

10.3 Possibility of hazardous reactions No hazardous reactions expected during normal use.

10.4 Conditions to avoidKeep away from sources of ignition, hot surfaces and

direct sunlight. Contact with incompatible materials.

10.5 Incompatible materials Oxidising agents.

10.6 Hazardous decomposition products Combustion may liberate toxic fumes: Carbon monoxide,

carbon dioxide, various hydrocarbons.

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity Harmful if swallowed.

ATE (oral): 1,190 mg/kg.

Skin corrosion/irritationCauses skin irritation.

Serious eye damage/irritation Causes serious eye damage.

Skin sensitisation May cause an allergic skin reaction.

Respiratory sensitisation No evidence of respiratory sensitisation.

Germ cell mutagenicityNo evidence of mutagenicity.

Carcinogenicity Suspected of causing cancer.

Reproductive toxicityNo evidence of reproductive toxicity.

Specific Target Organ Toxicity – single

exposure

Inhalation of high concentrations of vapour may cause

irritation to the respiratory tract.

Specific Target Organ Toxicity – Based on the available data, the classification criteria

XO1535HO Premium Heating Oil Additive + Fragrance



repeated exposure are not met.

Aspiration hazard May be fatal if swallowed and enters airways. Risk of

aspiration into lungs resulting in chemical pneumonia.

Information on likely routes of exposure

Inhalation Inhalation of high concentrations of vapour may cause

irritation to the respiratory tract.

Skin contact Causes skin irritation. May cause an allergic skin

reaction.

Eye contact Causes serious eye damage.

Ingestion Harmful if swallowed. Ingestion may cause irritation to

mouth, throat and digestive tract. May be fatal if swallowed and enters airways. Risk of aspiration into

lungs resulting in chemical pneumonia.

Symptoms related to the physical, chemical

and toxicological characteristics

Skin contact causes redness and pain. Skin contact may cause rash. Eye contact causes burns, watering, redness and pain. Inhalation of high concentrations of vapour may cause irritation to the respiratory tract. Ingestion may cause irritation to mouth, throat and digestive tract. If swallowed, aspiration into lungs may

result in chemical pneumonia.

Mixture versus substance information No data available.

Other information None.

SECTION 12: Ecological Information

12.1 Toxicity Toxic to aquatic life with long lasting effects.

No data available on the mixture.

12.2 Persistence and degradability No data available.

12.3 Bioaccumulative potential No data available.

12.4 Mobility in soil No data available.

12.5 Results of PBT and vPvB The product does not contain substances assessed to

XO1535HO Premium Heating Oil Additive + Fragrance

According to Regulation (EC) No. 1907/2006 (REACH)

assessment be PBT or vPvB.

12.6 Other adverse effects None known.

SECTION 13: Disposal Considerations

13.1 Waste treatment methods

To be disposed of as hazardous waste. Disposal should be in accordance with local, state or national legislation.

Contaminated adsorbent must be removed in sealed, plastic lined drums and disposed of via an authorised waste disposal contractor. Do not empty into drains; dispose of this material and its container in a safe way.

SECTION 14: Transport Information

ADR		
14.1	UN Number	3082
14.2	UN Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains 2,6-di-tert-butylphenol)
14.3	Transport hazard class(es)	9
14.4	Packing group	III
14.5	Environmental hazards	Yes
14.6	Special precautions for the user	Read SDS and supplier instructions on correct use of the product.
ADN		
14.1	UN Number	3082
14.2	UN Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains 2,6-di-tert-butylphenol)
14.2 14.3	UN Proper shipping name Transport hazard class(es)	•
		LIQUID, N.O.S. (contains 2,6-di-tert-butylphenol)
14.3	Transport hazard class(es)	LIQUID, N.O.S. (contains 2,6-di-tert-butylphenol) 9
14.3 14.4	Transport hazard class(es) Packing group	LIQUID, N.O.S. (contains 2,6-di-tert-butylphenol) 9
14.3 14.4 14.5	Transport hazard class(es) Packing group Environmental hazards	LIQUID, N.O.S. (contains 2,6-di-tert-butylphenol) 9 III Yes Read SDS and supplier instructions on correct use of

XO1535HO Premium Heating Oil Additive + Fragrance

ENVIRONMENTALLY HAZARDOUS SUBSTANCE,

LIQUID, N.O.S. (contains 2,6-di-tert-butylphenol)

14.2 UN Proper shipping name

According to Regulation (EC) No. 1907/2006 (REACH)

14.3	Transport hazard class(es)	9
14.4	Packing group	III
14.5	Environmental hazards	Yes
14.6	Special precautions for the user	Read SDS and supplier instructions on correct use of the product.
ΙΔΤΔ	(ICAO	

14.1	UN Number	3082
14.2	UN Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains 2,6-di-tert-butylphenol)
14.3	Transport hazard class(es)	9
14.4	Packing group	III
14.5	Environmental hazards	Yes
14.6	Special precautions for the user	Read SDS and supplier instructions on correct use of the product.

Version: 2.0 Date: 10/10/2012

IMDG		
14.1	UN Number	3082
14.2	UN Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains 2,6-di-tert-butylphenol)
14.3	Transport hazard class(es)	9
14.4	Packing group	III
14.5	Environmental hazards	Marine pollutant.
14.6	Special precautions for the user	Read SDS and supplier instructions on correct use of the product.
14.7	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	The product is not intended to be transported in bulk.

SECTION 15: Regulatory Information

15.1	Safety, health and environmental regulations/legislation specific for the substance or mixture	This Safety Data Sheet was prepared in accordance with EC Regulation (EC) No. 1907/2006 as amended. The product has been classified in accordance with Regulation (EC) No. 1272/2008 (CLP), Directive 67/548/EEC & Directive 1999/45/EC.
15.2	Chemical Safety Assessment	Not applicable.



Tincknell Fuels Ltd

According to Regulation (EC) No. 1907/2006 (REACH)

SECTION 16: Other Information

Full text of relevant R-phrases and/or H-statements:

Hazard Statement(s): H226: Flammable liquid and vapour.

H301: Toxic if swallowed. H302: Harmful if swallowed.

H304: May be fatal if swallowed and enters airways.

H311: Toxic in contact with skin. H312: Harmful in contact with skin.

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage. H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H335: May cause respiratory irritation. H351: Suspected of causing cancer. H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects. H411: Toxic to aquatic life with long lasting effects.

Supplemental Hazard information None. **(EU):**

Risk phrase(s): R10: Flammable.

R21/22: Harmful in contact with skin and if swallowed.

R22: Harmful if swallowed. R24: Toxic in contact with skin.

R24/25: Toxic in contact with skin and if swallowed.

R34: Corrosive.

R36/38: Irritating to eyes and skin.

R38: Irritating to skin.

R40: Limited evidence of a carcinogenic effect.

R41: Risk of serious damage to eyes.

R43: May cause sensitisation by skin contact.

R65: Harmful: may cause lung damage if swallowed.

R50: Very toxic to aquatic organisms.

R50/53: Very toxic to aquatic organisms may cause long-term adverse effects in the aquatic environment. R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

term adverse effects in the aquatic environment.

According to Regulation (EC) No. 1907/2006 (REACH)

Abbreviations:

CAS: Chemical Abstracts Service;

EINECS: European Inventory of Existing Commercial Chemical Substances

PBT: Persistent, Bioaccumulative and Toxic. vPvB: Very Persistent and Very Bioaccumulative.

References:

Supplier's Safety Data Sheets for ingredients
Product formulation
Approved Classification and Labelling Guide (Sixth edition)
The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009
Regulation (EC) No. 1272/2008 of the European Parliament and of the council.
EH40/2005, 2nd Ed., 2011.

Disclaimer:

THE INFORMATION PRESENTED HEREIN IS BELIEVED TO BE ACCURATE, BUT IS NOT WARRANTED TO BE, WHETHER ORIGINATING WITH THE COMPANY OR NOT. RECIPIENTS ARE ADVISED TO CONFIRM, IN ADVANCE OF NEED, THAT THE INFORMATION IS CURRENT, APPLICABLE, AND SUITABLE TO THEIR CIRCUMSTANCES.

Version history:

Version: 2.0

Issue date: 10/10/2012

Previous Version: 1.0

Issue date of previous version: 18/11/2011

Sections changed from previous version: 1-16.